

## Utah Division of Air Quality New Source Review Section

## Form 23 Rotary Kiln Incinerator

Date	
Company	
Site /Source	

There are federal standards and guidelines that govern incineration of: Hospital/medical/infectious waste; municipal waste; commercial/industrial waste, cement kilns. Consult 40CFR60, Subparts AAAA, DDDD, E<sub>C</sub>, and F, as appropriate

General Information			
1.	Flow diagram designations of rotary kiln Incinerator	described on this form:	
2.	Manufacturer of Incinerator:	3. Model name and number:	
4.	Description of material burned:	5. Maximum amount of waste to be incinerated:    lb/hr	
6.	Estimated daily amount of waste to be incinerated:	7. Height of stack above grade:  ft	
8.	Height of tallest structures within 150 feet:	9. Primary burner used: ? Yes ? No Maximum rating BTU/hr	
10.	Secondary Burner used: ? Yes ? No Maxi	mum ratingBTU/hr	
11.	Pescription of Typical Waste to Be Incinerated:  Medical/hospital/infectious  Municipal Industrial Commercial		
	Operatio	nal Information	
12.	Average operation time of incinerator: hrs	s/day days/weekweeks/year	
13.	Maximum operation time of incinerator:	_ hrs/day days/weekweeks/year	
14.	Residence time: Primary sec, Seconda	ry sec	
15.	Proposed BACT (Best Available Control Technolog? Quench Tower? Heat Exchanger? Dry Scrubber DAQ Form 9? Wet Scrubber DAQ Form 9? Baghouse DAQ Form 10? Carbon Adsorption Unit	y):	

	E	mission I	nformatio	n
	1	6. Averaç	ge Operatio	n
Contaminant t	Concentration or Emi	ssion Rate	per	Method Used to Determine Concentration or Emission Rate
Particulate matter	gr/dscf	? lb/1 ? lb/h	0 <sup>6</sup> BTU r	
Carbon Monoxide	ppm (vol)	? lb/1 ? lb/h	0 <sup>6</sup> BTU r	
Nitrogen Oxides	ppm (vol)	? lb/1 ? lb/h	0 <sup>6</sup> BTU r	
Organic material	ppm (vol)	? lb/1 ? lb/h	0 <sup>6</sup> BTU r	
Sulfur Dioxide	ppm (vol)	? lb/1 ? lb/h	0 <sup>6</sup> BTU r	
	16. (0	cont.) Max	imum Oper	ation
Contaminant	Concentration or Emission Rate per Identical Source			Method Used to Determine Concentration or Emission Rate
Particulate matter	gr/dscf	? lb/ ? lb/	10 <sup>6</sup> BTU hr	
Carbon Monoxide	ppm (vol)	? lb/ ? lb/	10 <sup>6</sup> BTU hr	
Nitrogen oxides	ppm (vol)	? lb/10 <sup>6</sup> BTU ? lb/hr		
Organic material	ppm (vol)	? lb/10 <sup>6</sup> BTU ? lb/hr		
Sulfur Dioxide Hydrogen Chloride	ppm (vol)	? lb/10 <sup>6</sup> BTU ? lb/hr		
16. (cont.) Metals (Max. Operation)(Lbs/hr)				
Cadmium – milligram/dscf				
Lead			Dioxins/fur	rins
	17.	Exhaust P	oint Informa	ation
Flow diagram designat	tion(s) of exhaust point:			
Description of exhaust	point (location in relation	to buildings,	direction, ho	poding, etc.):
Exhaust height above grade:			Exhaust di	iameter:
Greatest height of nearby buildings: ft			Exhaust di	istance from nearest plant boundary: ft
Ave	Average Operation			Maximum Operation
Exhaust gas temperature:			Exhaust ga	as temperature:
Gas flow rate through each exhaust point:			Gas flow r	ate through each exhaust point:

Emissions Calculations (PTE)					
18.	18. Calculated emissions for this device				
	PM <sub>10</sub>	Lbs/hr	Tons/yr		
	NO <sub>x</sub>	Lbs/hr	Tons/yr		
	SO <sub>x</sub>	Lbs/hr	Tons/yr		
	VOC	Lbs/hr	Tons/yr		
	HAPs	Lbs/hr (sp	eciate)	Tons/yr (speciate)	
Sub	Submit calculations as an appendix.				

## NOTE: 1. Submit this form in conjunction with Form 1 and Form 2.

- 2. Call the Division of Air Quality (DAQ) at **(801) 536-4000** if you have problems or questions in filling out this form. Ask to speak with a New Source Review engineer. We will be glad to help!
- 3. Attach spec. sheets for all burners, pollution control equipment, etc.

## Instructions

- 1. Attach flow diagram of the described incinerator.
- 2. Supply the manufacturer of the incinerator.
- 3. Supply the model and number of the incinerator.
- 4. Please describe the source of waste to be incinerated.
- 5. Supply the maximum amount of waste to be incinerated.
- 6. Specify the daily amount of waste to be incinerated.
- 7. Indicate the height of the stack above ground level.
- 8. Indicate the height of tallest structure within 150 feet.
- 9. Supply the specifications for primary burner used.
- 10. Supply the specifications for secondary burner used.
- 11. Indicate the type of typical waste to be incinerated.
- 12. Supply the average operation time of the incinerator.
- 13. Supply the maximum operation time of the incinerator.
- 14. Supply the residence time in the primary and secondary chambers.
- 15. Indicate the control technology to be use. Submit the corresponding form, if available, for the control technology. Submit specifications for control technology which a form is not available for. Forms available upon request are the following:

 Form 3	Afterburners
 Form 4	Flares
 Form 5	Adsorption Unit
 Form 6	Cyclone
 Form 7	Condenser
 Form 8	Electrical Precipitators
 Form 9	Scrubber
Form 10	Fabric Filter

- 16. During average and maximum operation, specify the concentration or emission rate of the listed contaminants.
- 17. Supply the exhaust specifications listed.
- 18. Supply calculations for all criteria pollutants and HAPs. Use AP42 or Manufacturers data to complete your calculations.

f:\engineer\generic\23\_kiln.frm revised 1/23/03